



## BEARING PRECISION AXLE CORP.



105 mm x 160 mm x 26 mm KR22X10X24PP  
Cam Follower Bearing / Printing Machine Bearing  
10\*22\*24mm

Bearing No. 6021

6021 Bearing 2D drawings and 3D CAD models

Size	105x160x26 mm
Bore Diameter	105 mm
Outer Diameter	160 mm
Width	26 mm
d	105 mm
D	160 mm
B	26 mm
C	26 mm
r min.	2 mm
da min.	113 mm
Da max.	152 mm
ra max.	2.0 mm
Weight	1.60 Kg
Basic dynamic load rating (C)	72,5 kN
Basic static load rating (C0)	65,5 kN
(Grease) Lubrication Speed	4000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0



## BEARING PRECISION AXLE CORP.

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	105MM Bore; 160MM Outside Diameter; 26MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nachiamerica.com">http://www.nachiamerica.com</a>
Outer Race Width	1.024 Inch   26 Millimeter
Outside Diameter	6.299 Inch   160 Millimeter
Bore	4.134 Inch   105 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	105 mm
Width	26 mm
Fillet Radius/Chamfer	2 mm
Dynamic Load Rating	72,500 N



## BEARING PRECISION AXLE CORP.

Static Load Rating	65,500 N
Limiting Speed - Grease	4,000 rpm
Limiting Speed - Oil	4,800 rpm
Factor $f_0$	15.8
Radial Clearance	0.015 to 0.041 mm
da (min)	113 mm
Da (max)	152 mm
ra (max)	2 mm