



BEARING PRECISION AXLE CORP.



7204A5TRDULP4Y Bearing 2D drawings and 3D CAD models

0.787 Inch | 20 Millimeter x 1.85 Inch | 47 Millimeter x 1.102 Inch | 28 Millimeter Rsl183040 Single-Row Full Complement Cylindrical Roller Bearing 200x287.75x82mm

Bearing No. 7204A5TRDULP4Y

Category	Precision Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight	0.2
EAN	0029176581021
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 7 ISO P4
Material - Ball	Steel
Number of Bearings	2 (1 Pair)
Contact Angle	25 Degree
Preload	Light
Raceway Style	1 Rib Outer Ring
Cage Material	Phenolic
Rolling Element	Ball Bearing
Mounting Arrangement	Duplex-Universal
Flush Ground	Yes
Inch - Metric	Metric
Other Features	Single Row Angular Contact Bore and OD are Exclusive All Others are ISO 4
Long Description	20MM Bore; 47MM Outside Diameter; 28MM



BEARING PRECISION AXLE CORP.

	Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball Material; 2 (1 Pair) Bearings; 25 Degree Contact Angle; Phenolic Cage Material; 1 Rib Outer Ring Rac
Category	Precision Ball Bearings
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact Ball
Manufacturer URL	http://www.nskamericas.com
Manufacturer Item Number	7204A5TRDULP4Y
Weight / LBS	0.441
D	1.85 Inch 47 Millimeter
B	1.102 Inch 28 Millimeter
d	0.787 Inch 20 Millimeter
bore diameter:	20 mm
radial dynamic load capacity:	1480 kgf
outside diameter:	47 mm
radial static load capacity:	845 kgf
overall width:	14 mm
maximum rpm:	22000 RPM
contact angle:	25 °
cage material:	Synthetic Resin
internal clearance:	C0
finish/coating:	Uncoated
ball screw application:	Not for Ball Screws
outer ring width:	14 mm
closure type:	Open
fillet radius:	1 mm
precision rating:	ABEC 7 (ISO Class 4)



BEARING PRECISION AXLE CORP.

series:	72
---------	----